

SharkBiteTM Brass Angle Stop Valve

SharkBite[™] expansion fittings are designed for use with PEX-a tubing and must be used in conjunction with SharkBite expansion rings. SharkBite expansion fittings have a 25-year system warranty when used with SharkBite PEX-a tubing.

Approved Applications

Residential and commercial potable water, recirculation, reclaimed water systems, hydronic heating/cooling (up to 50% glycol concentration) and direct burial.

Specification Data

Materials		
Valve Bonnet	Lead-Free DZR Brass	
Seal Ring	PTFE	
Valve Body	Lead-Free DZR Brass	
Plastic Jacket	PE	
Seal Ring	PTFE	
Ball	Lead-Free DZR Brass	
O-ring	NBR	
Valve Stem	Lead-Free DZR Brass	
Handle	Steel	
Screw	SST 302	
Sleeve	Copper	
Nut	Lead-Free DZR Brass	

Performance			
Max Working Pressure			
80 psi	at	200°F	
100 psi	at	180°F	
160 psi	at	73.4°F	

Minimum Length of Pipe Connecting Two Fittings			
Fittings/Pipe Size	Min. Length	Insertion Depth	
1/2 in.	4 in.	0.72 in.	
3/4 in.	5-1/2 in.	0.97 in.	
1 in.	7 in.	1.19 in.	
1-1/4 in.	9 in.	1.46 in.	
1-1/2 in.	11 in.	1.72 in.	
2 in.	14 in.	2.17 in.	

Certifications & Listings

ASME A112.18.1/CSA B125.1, NSF/ANSI 14, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372 For listing information, please contact Customer Service.

US 1877700 4242 | sales@sharkbite.com | sharkbite.com Canada 1888 820 0120 | canadasales@rwc.com

Dimensions (inches)				
Part #	Size	A	В	С
UAB23058	1/2" x 3/8" Compression	2.10	2.40	1.71

Product Submittal			
Name			
Date			
Architect/Owner			
Contractor			
Тад			
Notes			

Rev 2.0 / 12-9-22 Page 1 of 1 EN-US

