

## SharkBite<sup>TM</sup> Poly Reducing Coupling

SharkBite<sup>™</sup> expansion fittings are designed for use with PEX-a tubing and must be used in conjunction with SharkBite expansion rings. SharkBite expansion fittings have a 25-year system warranty when used with SharkBite PEX-a tubing.

## **Approved Applications**

Residential and commercial potable water, recirculation, reclaimed water systems, hydronic heating/cooling (up to 50% glycol concentration) and direct burial.

## **Specification Data**


Materials			
Body		PPSU	
Performance			
Max Working Pressure			
80 psi	at	200°F	
100 psi	at	180°F	
160 psi	at	73.4°F	

Minimum Length of Pipe Connecting Two Fittings					
Fittings/Pipe Size	Min. Length	Insertion Depth			
1/2 in.	4 in.	0.72 in.			
3/4 in.	5-1/2 in.	0.97 in.			
1 in.	7 in.	1.19 in.			
1-1/4 in.	9 in.	1.46 in.			
1-1/2 in.	11 in.	1.72 in.			
2 in.	14 in.	2.17 in.			

## **Certifications & Listings**

ASTM F1960, ASTM F877, CSA B137.5, NSF/ANSI 14, NSF/ANSI/CAN 61, NSF/ANSI/CAN 372, ASTM E84, CAN/ULC S102.2, ASTM E119, CAN/ULC S101

For listing information, please contact Customer Service.



Dimensions (inches)					
Part #	Size	Α	В		
UA058	3/4" x 1/2"	1.80	1.25		
UA060	1" x 3/4"	2.28	1.38		

Product Submittal			
Name			
Date			
Architect/Owner			
Contractor			
Tag			
Notes			

US 1877700 4242 | sales@sharkbite.com | sharkbite.com Canada 1888 820 0120 | canadasales@rwc.com Rev 1.0 / 06-23-22 Page 1 of 1 EN-US



This information is proprietary to RWC and is subject to change without notice. It may not be reproduced in part or whole without written authorization.