


# SharkBite<sup>™</sup> PEX-a Blue PEX-a Tubing

SharkBite $^{TM}$  PEX-a is a cross-linked polyethylene tubing designed for use in residential and commercial applications.

# **Specification Data**



Tubing Dimensions						
Nominal Size (CTS)	O. D. (in)	Wall Thickness (in)	Approx. I.D. (in)	Weight per ft. (lb.)	Volume per ft. (gal.)	
1/2"	0.625 ± 0.004	0.070 + 0.010	0.475	0.053	0.009	
3/4"	0.875 ± 0.004	0.097 + 0.010	0.671	0.102	0.018	

Tolerances referenced from ASTM F876.

## **Applications**

Potable water distribution, radiant heating, direct burial, embedded in concrete, snow & ice melting, geothermal groundloops, turf conditioning, municipal water service lines, fire suppression & plenum application.

#### **Materials**

Cross-Linked Polythethylene / PEX-a / Peroxide Method

Materials Designation Code - PEX 5106				
(5) Chlorine Resistance	Rated to continuously recirculate hot water at 140°F (40°C)			
(1) UV Resistance	One -month UV resistance			
	160 psi @ (33°F - 70°F) (0.5°C - 21°C)			
(06) Hydrostatic Stress	100 psi @ 180°F (80°C)			
	80 psi @ 200°F (93°C)			

# **Certifications & Listings**

ASTM F876, ASTM F877, NSF/ ANSI 14, NSF/ANSI/CAN 61, NSF/ ANSI/CAN 372, ASTM F2023, ASTM F2657, CSA B137.5, ASTM E84CAN/ULC S102.2, ASTM E119CAN/ULC S101



Refer to local plumbing code

Part number and description				
Part #	PEX Tubing (Coil)			
UA60B100	1/2" 100' Coil			
UA60B300	1/2" 300' Coil			
UA70B100	3/4" 100' Coil			
UA70B300	3/4" 300' Coil			
LIASOBIOO	1" 100' Coil			

Part #	PEX Tubing (Straight Length)
UA60B10	1/2" 10' Straight Length
UA60B20	1/2" 20' Straight Length
UA70B10	3/4" 10' Straight Length
UA70B20	3/4" 20' Straight Length
UA80B20	1" 20' Straight Length

#### **Bend Radius**

Unsupported Bend Radius = 6 X O.D.

### **Expansion & Contraction Rate**

Expansion rate: 1.1" / 10°F / 100'

For more technical data, visit the product at: https://www.sharkbite.com/products/potable-pex-a

Product Submittal		
Name		
Date		
Architect/Owner		
Contractor		
Tag		
Notes		

Rev 1.1 / 01-21-22

EN-US

